

TYPE	SAME DIMENSIONS AS YUASA TYPE	CAPACITY (Ah) 10HR	DIMENSION (±2MM)			WEIGHT (KG)	REGULAR CHARGE CURRENT (A)	ASSEMBLY FIGURE	TERMINAL TYPE	CCA @-18℃
			L	W	H					
(6 VOLT)										
YG6-4-2A	6N4-2A	4	71	71	94	0.85	0.4		-	30
YG6-6-3B	6N6-3B	6	98	56	116	1.35	0.6		5	60
YG6N11A-3A	6N11A-3A	11	119	59	128	1.87	1.10		5	120
YG6N11A-1B	6N11A-1B	11	119	59	128	1.86	1.10		5	120
(12 VOLT)										
YG2.5L-C	YB2.5L-C	2.5	80	70	105	1.03	0.25		-	30
YG3L-A	YB3L-A/YB3L-B	3	98	56	109	1.24	0.30		5	35
YG4L-B	YB4L-B	4	120	71	91	1.66	0.40		4	60
YG4HL-B	YB4L-B	5	120	71	91	1.72	0.50		4	70
YG5-C		5	152	50	106	1.87	0.5		22	80
YG5L-B	YB5L-B	5	120	60	128	1.79	0.50		22	80
YG5.5H-A2	12N5.5-4A	6.5	135	60	130	2.33	0.65		4	90
YG5.5-3B	12N5.5-3A/12N5.5-3B	6.5	135	60	130	2.33	0.65		4	90
YG6.5L	YTX6.5L-BS	6.5	139	66	101	2.28	0.65		5	70
YG7A-3A	YB7BL-B	7	149	59	130	2.57	0.70		22	120
YG7A-4A	YB7B-B	7	149	59	130	2.57	0.70		22	120
YG7A-A2	YB7A-A2	7	149	60	130	2.45	0.70		4	100
YG7C-A	YB7C-A	8	129	89	114	2.92	0.80		1	95
YG7-A	YB7-A/YB7-B	8	135	75	135	2.82	0.80		9	120
YG7L-A	YB7L-A	8	135	75	135	2.82	0.80		9	120
YG9L-B	12N9-3A/B, YB9L-A/B	9	135	75	139	3.02	0.90		9	130
YG9-B	12N9-4B-1, YB9-A/B	9	135	75	139	3.02	0.90		9	130
YG10L-A2	YB10L-A2/B2	11	134	88	145	3.99	1.10		9	170
YG10A-A2	YB10A-A2	11	134	88	155	4.10	1.10		9	170
YG10AL-A2	YB10AL-A2	11	134	88	155	4.10	1.10		9	170
YG12AL-A	YB12AL-A	12	134	80	161	4.39	1.20		5	145
YG12A-A	12N12A-4A1,YB12A-A/B	12	134	80	161	4.39	1.20		5	145
YG12A-A2	YB12A-A2	12	134	80	161	4.25	1.20		4	170
YG12C-A	YB12C-A	12	134	80	175	4.27	1.20		4	170
YG12AL-A2	YB12AL-A2	12	134	80	161	4.25	1.20		4	170
YG14-A2	YB14-A2	14	134	88	166	4.89	1.40		9	230
YG14L-A2	YB14L-A2, 12N14-3A	14	134	88	166	4.89	1.40		9	230
YG14A-A1	YB14A-A1	13	134	88	176	4.51	1.30		5	170
YG14A-A2	YB14A-A2	14	134	88	176	5.06	1.40		9	210
YG14AL-A2	YB14AL-A2	14	134	88	176	5.06	1.40		9	210
YG16AL-A2	YB16AL-A2	16	205	70	162	5.86	1.60		6	190
YG16A-AB	HYB16A-AB	16	150	90	180	5.02	1.60		6	145
YG51913 △	51913	21	183	79	171	6.11	2.10		3	300
YG50-N18A-A *	Y50-N18A-A	20	205	87	166	7.46	2.00		6	240
YG50-N18-A	Y50-N18-A/A3	20	205	87	162	7.46	2.00		6	240
YG50-N18L-A	Y50-N18L-A/A3	20	205	87	162	7.46	2.00		6	240
YG30CL-B	YB30CL-B	30	168	132	192	10.45	3.00		9	335
YG4A-BS	YTR4A-BS	2.5	110	47	85	1.06	0.25		10	35
YG4B-BS	YT4B-5	2.3	113	39	86	0.96	0.23		11	30
YG4L-BS	YTX4L-BS	4	113	69	85	1.43	0.40		9	60
YG5L-BS	YTX5L-BS	5	113	69	105	1.80	0.50		9	90
YG7L-BS	YTX7L-BS	7	113	69	130	2.41	0.70		9	120
YG7A-BS	YTX7A-BS	7	150	86	94	2.49	0.70		9	125
YG9-BS	YTX9-BS	9	150	86	105	2.93	0.90		9	145
YG9L-BS	YTX9L-BS	9	150	86	105	2.93	0.90		9	145
YG12A-BS	YTX12A-BS	10	151	87	105	3.32	1.00		9	145
YG12-BS	YTX12-BS	12	150	86	130	4.06	1.20		9	170
YG12L-BS	YTX12L-BS	12	150	86	130	4.06	1.20		9	170

YG14-BS	YTX14-BS	14	150	86	145	4.59	1.40	#TTTT#	9	205
YG14L-BS	YTX14L-BS	14	150	86	145	4.59	1.40	#TTTT#	9	205
YG15-BS	YTX15-BS	14	175	87	130	4.82	1.40	#TTTT#	4	215
YG15L-BS	YTX15L-BS	14	175	87	130	4.82	1.40	#TTTT#	4	215
YG16-BS-1	YTX16-BS-1	14	151	87	161	5.15	1.40	#TTTT#	1	170
YG16-BS	YTX16-BS	16	150	86	161	5.22	1.60	#TTTT#	9	220
YG16L-BS	YTX16L-BS	16	150	86	161	5.22	1.60	#TTTT#	9	220
YG20CH-BS	YTX20CH-BS	18	151	87	161	5.96	1.80	#TTTT#	9	215
YG18-BS	YTX18-BS,YIX50-BS	20	205	87	162	7.46	2.00	#TTTT#	4	275
YG18L-BS	YTX18L-BS,YIX50L-BS	20	205	87	162	7.46	2.00	#TTTT#	4	275
YG19-BS	YB16-B	19	175	100	155	6.47	1.90	#TTTT#	4	230
YG19L-BS	YB16L-B	19	175	100	155	6.47	1.90	#TTTT#	4	230
YG19CL-BS	YB16CL-B	21	175	100	175	7.57	2.10	#TTTT#	4	250
YG20-BS	YTX20-BS/YTX20H-BS	20	175	87	154	6.29	2.00	#TTTT#	9	290
YG20L-BS	YTX20L-BS/YTX20HL-BS	20	175	87	154	6.29	2.00	#TTTT#	9	290
YG24HL-BS	YTX24HL-BS	24	205	87	162	7.50	2.40	#TTTT#	4	335
YG30-BS	YIX30-BS	30	167	127	176	9.53	3.00	#TTTT#	4	360
YG30L-BS	YIX30L-BS/YB30L-B	30	167	127	176	9.53	3.00	#TTTT#	4	360
YG53030	53030	28	178	123	166	8.64	2.80	#TTTT#	3	325
YG53034	53034	28	178	123	166	8.64	2.80	#TTTT#	3	325
YG52430	12N24-3/12N24-3A	24	178	123	166	7.71	2.40	#TTTT#	3	290
YG52434	12N24-4/12N24-4A	24	178	123	166	7.71	2.40	#TTTT#	3	290
YG60-N30-BS	Y60-N30-A/Y60-N30-B	30	186	130	170	9.54	3.00	#TTTT#	3	335
YG60-N30L-BS	Y60-N30L-A/Y60-N30L-B	30	186	130	170	9.54	3.00	#TTTT#	3	335
YG7B-4	YT7B-4/YT7B-BS	6	150	65	92	2.44	0.60	#TTTT#	9	70
YG9B-4	YT9B-4/YT9B-BS	8	150	69	105	2.96	0.80	#TTTT#	9	90
YG12B-4	YT12B-4/YT12B-BS	10	150	69	130	3.68	1.00	#TTTT#	9	125
YG14B-4	YT14B-4/YT14B-BS	12	150	69	145	4.27	1.20	#TTTT#	9	130
YG3ZS	YTZ5S	3	114	70	85	1.40	0.30	#TTTT#	4	35
YG5ZS	YTZ5S	4	113	69	85	1.45	0.40	#TTTT#	9	65
YG6ZS	YTZ7S	6	113	69	105	1.93	0.60	#TTTT#	9	95
YG7ZS	YTZ7S	6	113	69	105	1.93	0.60	#TTTT#	9	95
YG10ZS	YTZ10S	8.6	150	86	94	2.77	0.86	#TTTT#	9	145
YG12ZS	YTZ12S	11.2	150	86	110	3.38	1.12	#TTTT#	9	170
YG14ZS	YTZ14S	11.2	150	86	110	3.38	1.12	#TTTT#	9	170
YG15ZS	YTZ15S	15	150	87	144	4.85	1.50	#TTTT#	23	205
YG16ZS	YTZ16S	16	150	86	145	4.65	1.60	#TTTT#	9	240

With adaptor from terminal type 5 to type 7.

* The height includes 4mm spacer.

△ 20 hour rate

